

HR17i Activation + Safety



Highly manoeuvrable detection area at mounting heights of up to 6m



Unprecedented combined door activation and pedestrian safety at mounting heights of up to 6m

Construction Free Door Opening


Replace in-ground loop detectors by providing identical features in an easy to install overhead mounted device

Unparalleled Pedestrian Safety

Pivoted sensor head allows a static presence detection area to be focused directly in front of the door close zone

Eliminate Door/Goods Damage

Infinity presence timer prevents door closures on static objects left in the door close zone















Technical Specification

Accessories



Cable 12M Hotron 12M Cable

Model	HR17i Industrial Door Activation + Safety	
Detection Method	Active Infrared Detection	
Installation Height	Max 3000mm to 6000mm (9.8ft to 19.7ft)	
Sensor Dimensions	114mm (W), 145mm (H), 108mm (D)	
Pattern Adjustment	Width Adjustment: Wide or Narrow Pattern (Dip Switch)	
	Width Adjustment: Left or Right (Flexible sensor head)	
	Depth Adjustment: 3 or 4 rows of detection (Dip Switch)	
	Depth Adjustment: Up or Down (Flexible sensor head)	
Presence Timer	2sec, 1min, 10min and infinity (all 4 rows)	
IP Rating	55	
Power Supply	12 to 24V AC or DC \pm 10%	
Power Consumption	AC12V-2.5 [VA] (Max), DC12V-150 [mA] (Max)	
	AC24V-2.8 [VA] (Max), DC24V-75 [mA] (Max)	
Output Relay	Relay contact: DC30V 2A (Resistance Load)	
Relay Hold Time	Approx. 0.5 sec	
LED Indication	Indicator LED: Power On	= Red On
	Indicator LED: Detecting	= Red Off
	Indicator LED: Self Diagnostics	= Red Flashing
	Reflection level monitor LED Normal	= Red Off
	Reflection level monitor LED High Reflection	= Red On
Operating Temperature	-20°C to +55°C, (-4°F to 131°F)	
Weight	380g (0.83 lbs)	
Available Colours	White: Product Code	= HR17i-12M
Accessories Provided	12m Connection Cable, Mounting Template, Mounting Screws, Installation Instructions	

Detection Area (inches/mm)

